

HARMSCO® MUNICIPAL

Meet your **EPA** LT2 requirements today.

Harmsco® LT2 cartridges and housings exceed the three-log (99.9%) removal requirement described in LT2 ESWTR Toolbox Guidance Manual 8.4.1. for cyst-sized particles.

Hurricane® Design saves up to 20% Energy Costs!

APPROVED SYSTEMS:



- Alaska
- Colorado
- Montana
- New York
- Oregon
- Texas
- Washington



Certified to ANSI-NSF 61

Certified: NSF/ANSI Standard 61
Drinking Water System Components - Health Effects



Municipal LT2 Options 3.6 Log Removal

Filter Model	NO. of Elements	Pleated Media Area (sq.ft.)	Max Flow Rate (GPM)	Max Flow Rate (LPM)	Max Flow Rate (M ³ /HR)
MUNI-1-2FL-304	1	120	100	378	23
MUNI-3-3FL-304	3	360	300	1,135	68
MUNI-5-4FL-304	5	600	500	1,892	113
MUNI-8-6FL-304	8	960	800	3,028	181

Hurricane® Video
www.harmsco.com/z/100

Call to learn about Harmsco's Cost-effective Solutions for LT2 Compliance.



Proudly distributed by: MAC Water Technologies, Inc.
P.O. Box 416 Shawnee Mission, KS 66201 • 913-375-3483
rmcafee@macwaterech.com • tball@macwatertech.com



Made in USA

LT2

3.6 Log Removal

Meets Long Term 2 (LT2) Requirements for Ground Water Under Direct Influence of Surface Water (GWUDI)

- ▶ High flow capability
- ▶ Low initial pressure drop
- ▶ Lower overall operating cost
- ▶ Increased contaminant removal
- ▶ Longer filter runs for fewer change-outs

Cyst-free Drinking Water

APPROVED SYSTEMS:



- Alaska
- Colorado
- Montana
- New York
- Oregon
- Texas
- Washington



Certified: NSF/ANSI Standard 61
Drinking Water System Components - Health Effects

Pleated LT2 Cartridges

Results of Challenge Test Conducted by IBR

Cartridge Tested	Filter Housing	Tested Flow Rate	Sample Point	Minimum Log Removal
HC/170-LT2	MUNI-1-2FL-304	100 GPM	Initial Efficiency	3.6
			50% Terminal Pressure Drop: 15 psi	3.8
			100% Terminal Pressure Drop: 30 psi	3.7

NOTE: This publication is to be used as a guide. The data within has been obtained from many sources and is considered to be accurate. Harmsco does not assume liability for the accuracy and/or completeness of this data. Changes to the data can be made without notification. Temperature, Pressure, Flow Rates, Differential Pressures, Chemical Combinations and other unknown factors can affect performance in unknown ways. **Limited Warranty:** Harmsco warrants their products to be free of material and workmanship defects. Determination of suitability of Harmsco products for uses and applications contemplated by Buyer shall be sole responsibility of Buyer. The end user/installer/buyer shall be liable for the product's performance and suitability regarding their specific intended applications. End users should perform their own tests to determine suitability for each application.



MAC WATER Technologies, Inc.
Impurities Removed,
Quality Service Added.

Proudly distributed by: MAC Water Technologies, Inc.
P.O. Box 416 Shawnee Mission, KS 66201 • 913-375-3483
rmcafee@macwatertech.com • tball@macwatertech.com